

## GILCO MULTI-PURPOSE GL-1 GEAR LUBRICANT SAE 90 AND 140

### DESCRIPTION AND APPLICATIONS

**GILCO Multi-Purpose GL-1 Gear Lubricant** is manufactured with high quality base stocks to provide oxidation stability for long service life. This oil is inhibited against foaming and does not contribute to corrosion or wear of yellow metals, such as brass or bronze.

This product meets API designation GL-1. It is designed for use in manual transmissions and transfer cases in on-highway trucks and off-highway equipment, which require an API GL-1 gear lubricant. It may also find use in industrial gear oil applications that call for a straight mineral oil in the SAE 50 engine oil or SAE 90 viscosity weight range. (The SAE 50 engine oil viscosity grade is approximately equal to the SAE 90 gear oil viscosity grade).

### Directions for use:

Fill up the reservoir with **GILCO Multi-Purpose GL-1 Gear Lubricant**. Always follow the manufacturer recommendations.

### Product Specifications:

<i>Typical</i>	<b>GL-1 90</b>	<b>GL-1 140</b>
Specific Gravity, (H <sub>2</sub> O=1)	0.90	0.91
Viscosity, @ 100°C, cSt	17.9	26.8
Viscosity Index, min.	40	60
Flash Point, °F(°C)	400	(204) 400
Pour Point, °C(°F)	-18	(0) -18
Color	4.5	(204) (0) 4.5

### Packaging Specifications:

Bottle	1 gal HDPE plastic bottle; 5 gal pails
Case Size	N/A
Pallet size	N/A

### Product Claims:

**GILCO Multi-Purpose GL-1 Gear Lubricant** meets API GL-1 designation for gear lubricants. This product is not corrosive to yellow metal, maintains oil film strength at wide range of operating temperatures, resists foaming and minimizes rust formation.

### Hazards:

Do not pollute. Conserve resources, return used oil to collection centers. Avoid prolonged contact with skin. In case of contact, wash hands thoroughly with soap and water. Keep out of reach of children.