
GILCO SA 30, 40 PREMIUM MOTOR OIL

DESCRIPTION AND APPLICATIONS

GILCO SA 30, 40 Premium Motor Oil is blended from selected virgin base oils and is designed to meet API service Designation "SA". It helps engines run cleaner and last longer while providing engine protection. Recommended for use in gasoline engines where API SA service is permitted.

Product Specifications:

	SA 30	SA 40
Specific Gravity (H ₂ O=1)	0.90-0.93	0.90-0.93
Viscosity, @ 100°C, cSt	10.6-11.6	12.6-16.3
Flash Point, °C (°F)	193 (380)	196 (385)
Pour Point, °C (°F)	-20 (-5)	-15 (+5)
Color	Amber	Amber
Odor	Petroleum	Petroleum

Packaging Specifications:

Bottle	32 fluid ounces (946 ml), HDPE plastic bottle
Case Size	N/A
Pallet size	N/A
Cases/Pallet	108
Units/Case	12

Product Claims:

GILCO SA 30, 40 Premium Motor Oil is recommended for straight mineral oil lubrication.

Hazards:

"Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressure, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. "Empty" drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner.

Avoid prolonged contact with skin and frequently change soiled clothing. In case of contact, wash thoroughly with soap and water for 15 minutes or until the irritation subsides. The formation of mists should be avoided.

CAUTION: Continuous contact with used motor oil has caused skin cancer in laboratory animals.

Keep out of reach of children.