

GILCO AW HYDRAULIC OIL

DESCRIPTION AND APPLICATIONS

GILCO AW Hydraulic Oil is economical hydraulic oil developed as a general purpose anti-wear, rust, corrosion, and oxidation inhibited oil, suitable for use where service requirements are normal to moderate and long-term heavy-duty protection is not critical. This oil is formulated with high quality, refined base stocks and select additives to provide wear protection and anti-foam properties.

<u>Product Specifications:</u>	<u>AW 32</u>	<u>AW 46</u>	<u>AW 68</u>	<u>AW 100</u>
Grade	32	46	68	100
API Gravity (60°F)	24.0	22.7	22.7	21.8
Oxidation Life, min, hrs	2000	2000	2000	2000
Viscosity, @40°C, cSt	41.0	41.0	67.0	82.0
Viscosity, @ 100°C, cSt	4.95	5.3	6.8	8.7
Flash Point, °C (°F)	154 (310)	163 (325)	163 (325)	168 (334)
Pour Point, °C (°F), max	-23 (-9)	-23 (-9)	-23 (-9)	-18 (0)
Color, typical	1.5	2.0	2.5	2.5

Packaging Specifications:

Bottle	HDPE plastic bottle
Cases/Pallet	N/A
Units/Case	N/A
Bulk	Available

Product Claims:

GILCO AW Hydraulic Oil is recommended for use in hydraulic systems utilizing radial or axial piston, vane, gear and other type pumps, where quality anti-wear hydraulic oil is required by equipment manufacturers.

Hazards:

"Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressure, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. "Empty" drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner. Avoid prolonged contact with skin and frequently change soiled clothing. In case of contact, wash thoroughly with soap and water for 15 minutes or until the irritation subsides. The formation of mists should be avoided. Do not take internally. If swallowed, do not induce vomiting. Call physician or Poison Control Center immediately. Keep out of reach of children.