

GILCO R & O HYDRAULIC OIL

DESCRIPTION AND APPLICATIONS

GILCO R & O Hydraulic Oil is high quality hydraulic oil developed as an anti-wear, rust, corrosion, and oxidation inhibited oil, suitable for use where service requirements are normal to moderate and long-term heavy-duty protection is not critical. Additive package designed to prevent the formation of gum, varnish and rust deposits and to prevent cavitation. This oil is formulated with premium quality, refined mid-range viscosity index base stocks and select additives to provide wear protection and anti-foam properties.

Product Specifications:

Specific Gravity (60°F)	0.88
Viscosity, @40°C, cSt	40.0
Viscosity, @ 100°C, cSt	5.4
Viscosity Index	49
Flash Point, °C (°F)	177 (350)
Pour Point, °C (°F)	-9 (16)
Color and Appearance	Clear light yellow liquid
Odor	Petroleum

Hazards:

"Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressure, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. "Empty" drums should be completely drained, properly bunged, and promptly returned to a drum reconditioner. Avoid prolonged contact with skin and frequently change soiled clothing. In case of contact, wash thoroughly with soap and water for 15 minutes or until the irritation subsides. The formation of mists should be avoided. Do not take internally. If swallowed, do not induce vomiting. Call physician or Poison Control Center immediately. Keep out of reach of children.